



# LBB 1941/00 Plena Call Station



- ▶ Stylish all-call call station, intended for LBB 1925/00 system pre-amplifier
- ▶ Unidirectional condenser microphone on flexible stem
- ▶ Momentary PTT- key for calls
- ▶ Selectable gain, speech filter and limiter for improved intelligibility
- ▶ Stable metal base design
- ▶ Fixed 5 m cable and loop-through connector for additional call stations.

The Plena call station is a stylish, high-quality call station with a stable metal base design, a flexible microphone stem and a unidirectional condenser microphone. It is intended for making calls to all zones (i.e. all-call) in a PA system built around the LBB 1925/00 system pre-amplifier. In addition to table-top use, the special design enables the unit to be neatly flush-mounted in desk tops.

## Parts Included

Quantity	Component
1	LBB 1941/00 Plena Call Station
1	5m cable terminated with a lockable 8-pin DIN connector
1	Loopthrough 8-pin DIN socket to add an additional call station LBB 1941/00 or LBB 1946/00

## Functions

A green LED on the call station gives visible feedback on the active state of the microphone.

This call station features selectable gain, a selectable speech filter and a limiter for improved intelligibility, even if the speaker moves in front of the microphone. The call station provides a balanced line level output, and can be positioned up to 500 m away from the amplifier using CAT-5 extension cables. Inside the LBB 1925/00 different priority levels and pre- and post-call chimes can be assigned for this call station.

## Certifications and Approvals

EMC emission	acc. to EN 55103-1
EMC immunity	acc. to EN 55103-2

## Technical Specifications

### Electrical

#### Power Supply

Voltage Range	18 – 24 V (24 V supplied by LBB1925/00)
Current Consumption	<30mA

#### Performance

Nominal Sensitivity	85 dB SPL (gain preset 0 dB)
Nominal Output Level	700 mV
Maximum Input Sound Level	110 dB SPL
Gain Preset	+6 / 0 / -15 dB
Limiter Threshold	2 V
Compression Ratio Limiter	1:20
Distortion	<0.6 % (maximum input)
Equivalent Input Noise Level	25 dB SPLA
Frequency Response	100 Hz – 16 kHz
Speech Filter	-3dB @ 315 Hz, high-pass, 6 dB / oct
Output Impedance	200 ohm

### Environmental

Operating Temperature	-10 to +55°C
Storage Temperature	-40 to +70°C
Relative Humidity	<95%
Dimensions	40 x 100 x 235 mm (base) 390mm stem length (with microphone)
Cable Length	5m
Weight	approx. 1 kg

## Ordering Information

### Model | Description

LBB 1941/00 Plena Call Station

**Americas:**  
Bosch Security Systems  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 585 223 4060  
Fax: +1 800 289 0096  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 (0) 40 27 83955  
Fax: +31 (0) 40 27 86668  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

### Represented by