




MVM-BVRM Video Recording Manager v2.20



- ▶ **Distributed storage and configurable load balancing**
- ▶ **iSCSI disk array failover for extra reliability**
- ▶ **Used with all Bosch Video-over-IP cameras and encoders**
- ▶ **Configuration support for all Bosch disk arrays (DVA, DSA and DLA series)**

Bosch Video Recording Manager (VRM) provides a Distributed Network Video Recorder solution, eliminating the need for dedicated NVRs and signaling the second generation of IP network video recording. VRM supports iSCSI-based storage systems and Bosch Video-over-IP devices (IP cameras and IP video encoders).

VRM introduces the concept of a storage virtualization layer. This abstraction layer enables VRM to manage all of the individual disk arrays in the entire system as a single “virtual” common pool of storage, which is intelligently allocated as needed.

VRM eliminates the need for Network Video Recorders (NVRs) and their associated server hardware, operating systems, and anti-virus software, as well as the ongoing software patches and updates these systems require.

This new technology makes installation, operation, and maintenance much easier while reducing the total cost of ownership.

System Overview

The Video Recording Manager is comprised of the

- Recording Management Service (VRM Server)
- Bosch Configuration Manager

The central Recording Management Service runs as a service on Microsoft Windows platforms. Bosch recommends running VRM Server on a dedicated server/hardware platform.

VRM offers system-wide recording, monitoring, and management of Bosch iSCSI storage, video encoders, and cameras.

VRM 2.20 software supports Bosch H.264 and MPEG-4 IP video devices including all encoders, Dinion and FlexiDome IP cameras, as well as AutoDome and Extreme IP cameras and the Bosch HD cameras. Supported storage subsystems include the Bosch iSCSI-based DVA, DSA and DLA Series disk array systems. The iSCSI disk arrays can be attached anywhere on a standard IP network.

VRM 2.20 offers additional redundancy and data availability by supporting Automatic Network Replenishment (ANR) with Bosch Video-over-IP devices (BVIP Firmware 4.0 or later required).

Optimal Performance

The Video Recording Manager offers a high-performance, flexible, scalable, and a highly reliable iSCSI storage management solution.

Optimized performance is obtained by the use of intelligent addressing on a block level, which also allows for load balancing of the video recording to all available storage blocks located on any storage array in the system.

Load balancing is provided with respect to the bandwidth and the number of iSCSI connections and is configurable per IP address (iSCSI target).

Logical Virtualization

The VRM virtualization layer allows the scalability of storage beyond the physical limits of a single storage subsystem. This logical abstraction layer means that each camera can use any storage space it actually needs, rather than an allocated, arbitrary, discrete chunk ahead of time. Adjust retention times of video data as required.

Fast Recording and Retrieval

VRM provides fast and flexible retrieval via a search database of recordings and metadata. Metadata is a form of data that describes other data such as events, ATM/POS information, and video content analysis data. The metadata is recorded with the video data and provides a fast and efficient way for the search engine, in the playback client, to quickly locate specified video clips. The database also keeps track of the location of recording blocks. If this database is lost, VRM can recreate the database by reading the stored metadata, thus providing a self-healing capability.

Distributed Storage


VRM not only provides for redundant management of metadata, it also introduces a significant enhancement of overall reliability and availability. By providing redundancy for storage provisioning and a failover design for the central recording management service, there is no single point of failure. In addition, unlike NVR systems, VRM scales without requiring additional PCs. This greatly reduces the risk of system failures.

Functions

VRM Server

VRM Server, with the central Recording Management Service, maintains a database containing the recording source information and a list of associated iSCSI drives. The central monitoring includes a Web-based user interface for status monitoring. This provides system status overview, recording status information, as well as for live view and recording preview for single cameras.

VRM Monitor



VRM Server

Bosch Configuration Manager

The Configuration Manager allows for central configuration of the network storage subsystems, recordings (including schedules), data rate, frame rate, stream, and privileges, as well as for managing user accounts.

Playback Client

For replay use Bosch Video Client BVC Version 1.1 or later. The BVC is available on the Bosch ST web site www.boschsecurity.com.

For more information about Bosch Video Client BVC, see the product specific documentation.

Automatic Network Replenishment ANR

A VRM server can perform maximum 3 ANR jobs simultaneously. If you configure multiple ANR jobs for 1 device (for example with 4 channels), these jobs are performed one after the other. This avoids overload of the device. The number of ANR jobs cannot be increased by a secondary VRM server. The maximum performance is 24-times of replay, the actual performance may be limited by the capabilities of the encoder/camera.

ANR is only effective for data within the minimum retention time of the system. Recording gaps outside the minimum retention time will not be considered.

Backup of data through VRM

A VRM server can execute maximum 5 backup jobs in parallel. The number of backup jobs cannot be increased by a secondary VRM server. The maximum performance is 24-times of replay. Consider this for bandwidth estimation of the iSCSI targets.

The backup functionality is not supported by BVMS or the BVC replay client.

Design Recommendations

Load Balancing (if VRM is configured in "All Mode")

VRM 2.20 provides a new server based "All Mode" (Automatic Mode).

If the previous video device based "All Mode" is used the following design recommendations should be observed:

When calculating the number of storage arrays for VRM environments we strongly recommend adding an additional iSCSI target (n+1 calculation) or using the "Failover Mode".

This recommendation is especially important when using the DLA Series because these storage systems provide a lower reliability and availability than the DSA Series.

ANR

The first implementation of ANR in VRM is suited to protect against single short network outages. One network outage must be longer than 10 seconds to be detected by the ANR mechanism. If the outages are shorter potential gaps are not detected and recording is not refilled.

ANR is not suited to be used for:

- Wireless applications because of frequent network outages.
- Mobile applications because of long outages with large recording gaps which takes very long to be filled.

Licensing

Existing VRM 2.0 licenses can be used for VRM 2.20.

Installation/Configuration Notes

VRM Components

The Video Recording Manager consists of the following components which may be installed on separate systems.

- VRM Server (central Recording Management Service) with Web interface for VRM Monitor
- Bosch Configuration Manager

VRM Monitor

- Displays overall system status information, including uptime, bit rate, and retention times.
- Provides status information on recordings and storage.
- Displays live view and recording previews for a single camera.

Bosch Configuration Manager

- Allows configuration of the iSCSI storage subsystems.
 - Bosch DVA Series (Bosch OEM Disk Arrays)
 - Bosch DSA Series (NetApp Storage Systems)
 - Bosch DLA Series (Bosch OEM Disk Arrays)
- Allows configuration of recording parameters, including schedules, data rates, frame rates, streams, and privileges.
- Allows management of users and groups with privileges and roles.
- Allows configuration of load balancing parameters (bandwidth and iSCSI connections) per disk array (IP address).

Technical Specifications

Bandwidth	1 Gbit network (recommended)
Supported languages	Arabic, Czech, English, German, Danish, Dutch, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Portuguese, Polish, Russian, Spanish, Simplified Chinese, Swedish, Thai, Traditional Chinese and Turkish

VRM Server (running as a service)

Supported operating systems

Windows 7 Ultimate, Professional Edition 32-bit, 64-bit versions
Windows Server 2003 R2, Standard Edition, 32/64-bit versions
Windows Server 2008 R2, Standard Edition 64-bit versions
Windows Storage Server 2008, Standard Edition 64-bit versions

Hardware requirements

CPU	Dual-Core Intel Xeon Processor 5110 (1.60 GHz, 1066 FSB) to Quad-Core Intel Xeon Processor E5430 (2.66 GHz, 1,333 FSB)
RAM	1 GB or more
Graphics card	VGA or SVGA-compatible
Network adapter	1 Gbps
Installation	Windows administrator rights
Recommended Bosch Server Hardware	< 100 cameras: MHW-S360R7-LL/LLUS < 350 cameras: MHW-S380R7-EL/ELUS > 350 cameras: MHW-S380R7-MC/MCUS

VRM Monitor

Browser	Replay only with Microsoft Internet Explorer, v8.0 or 9.0
Network adapter	1 Gbps
Software	DirectX 9.0c/MPEG Active X

Bosch Configuration Manager

Supported operating systems

Windows XP Professional SP3, 32-bit versions
Windows 7 Ultimate/Enterprise, 32/64-bit versions
Windows Server 2003 R2, Standard Edition with SP2, 32/64-bit versions
Windows Server 2008 R2, Standard Edition 64-bit versions
Windows Storage Server 2008, Standard Edition 64-bit versions

Hardware requirements

CPU	Intel Pentium (minimum 2.80 GHz) to Intel Core i3/i5/i7; Intel Xeon Dual Core or Quad Core (X3 or E3 Families)
RAM	256 MB or more
Graphics card	VGA or SVGA-compatible
Network adapter	1 Gbps
Software	DirectX 9.0c
Installation	Windows administrator rights

Note:

One VRM supports:

- 2048 channels
- 1 PB storage (net capacity)
- 40 disk arrays (recommended)
- maximum 128 iSCSI targets supported

When planning for larger environments we strongly recommend using large sized disk arrays instead of a large number of small disk arrays (vertical scaling instead of horizontal scaling). For systems with more than 40 disk arrays, please contact a Bosch Design Engineer. iSCSI based storage systems not qualified by Bosch are not supported.

Ordering Information

MVM-BVRM-016 Bosch VRM base package with a 16-camera license single-pack. VRM 2.0 licenses can be used for VRM 2.20.	MVM-BVRM-016
MVM-SVRM-BAK Bosch VRM Failover license. VRM 2.0 licenses can be used for VRM 2.20.	MVM-SVRM-BAK
MVM-XVRM-016 16-camera upgrade license	MVM-XVRM-016
MVM-XVRM-032 32-camera upgrade license	MVM-XVRM-032
MVM-XVRM-064 64-camera upgrade license	MVM-XVRM-064

Ordering Information

MVM-XVRM-128 128-camera upgrade license	MVM-XVRM-128
MVM-XVRM-256 256-camera upgrade license	MVM-XVRM-256
MVM-XVRM-512 512-camera upgrade license	MVM-XVRM-512
MVM-XVRM-1024 1024-camera upgrade license	MVM-XVRM-1024
MVM-XVRM-2048 2048-camera upgrade license	MVM-XVRM-2048

Accessories

MHW-S360R7-LL Management Server Entry-level server, standard performance (localization kit must be ordered separately)	MHW-S360R7-LL
MHW-S360R7-LLUS Management Server Entry-level server, standard performance, including US localization kit	MHW-S360R7-LLUS
MHW-S380R7-EL Management Server Mid-range server, advanced performance with internal hard disks (localization kit must be ordered separately)	MHW-S380R7-EL
MHW-S380R7-ELUS Management Server Mid-range server, advanced performance with internal hard disks, including US localization kit	MHW-S380R7-ELUS
MHW-S380R7-MC Management Server Upper-mid-range server, high performance (localization kit must be ordered separately)	MHW-S380R7-MC
MHW-S380R7-MCUS Management Server Upper-mid-range server, high performance, including US localization kit	MHW-S380R7-MCUS
MHW-AWLCK-DE Localization Kit Localization (OS/keyboard): Germany—German	MHW-AWLCK-DE
MHW-AWLCK-FR Localization Kit Localization (OS/keyboard): France—French	MHW-AWLCK-FR
MHW-AWLCK-IT Localization Kit Localization (OS/keyboard): Italy—Italian	MHW-AWLCK-IT
MHW-AWLCK-UK Localization Kit Localization (OS/keyboard): United Kingdom—British English	MHW-AWLCK-UK

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

Represented by