

23.6" FHD CCTV Monitor



LED technology benefits from intelligent color corrective technology with a mercury-free WLED backlight that automatically detects image signal and controls backlight brightness for blacker blacks purer whites and more clearly defined grays.

Features

- FHD display 1920 x 1080
- Excellent contrast ratio and brightness
- Built-in 3D comb-filter & 3D de-interlace
- VESA hole 100 x 100 (mm)
- PIP / PBP Multi-display function
- 2 x Composite BNC In / Out for looping
- Remote supported
- No Mercury. Environment-friendly Product
- LED backlit leads to less power consumption

Model	
General	
Diagonal size	23.6"
Panel type	TFT LCD
Aspect ratio	16:9
Number of pixels	1920 x 1080
Pixel pitch	0.2715 x 0.2715 mm
Color depth	16.7 Million Colors
Backlight	LED
Optical (typ.)	
Brightness	300 cd/m2
Contrast ratio	10000:1
Response time (Tr + Tf)	5 ms
Viewing angle	Vertical -85°~85° / Horizontal -80°~80°
Operation	
Input Interface	BNC x 2, HDMI x 1, VGA x 1
Output Interface	BNC x 2
Display mode	Video 1 / Video 2 / PC / HDMI
OSD	Picture Mode, Contrast, Brightness, Color, Tint, Sharpness, Color Temp, DNR
OSD Languages	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech
Speaker	1.5 W x 2
Remote control	YES
Composite Video	
System	
PAL / NTSC	
Video processing	Motion Adaptive 3D De-Interlacer and DNR, 4H Comb filter Y/C separation
Electrical	
AC power	AC 100-240V 50/60HZ
Power consumption	< 36W
Power supply	External power adapter
Mechanical	
Case material	Plastic
Dimension (W x H x D) (include stand)	580 x 428 x 164 mm
Support	Pedestal base
Mounting interface	100 x 100 mm , M4 x 4 holes
Net weight (Monitor & stand)	4.6Kgs (10.1 lbs)
Environment	
Temperature	Operation: 0°~40°C(32°~104°F) , Storage: -10°~60°C(14°~140°F)
Humidity	10%~90%
Safety	FCC, CE, ROHS
Delivery set	Monitor, Power cord with adapter, VGA cable, Remote controller, User Manual

Input / Output



Physical Drawing

