



| | | | | | | | | | | | |
|---|------|----------|---------------|----------|---------|------------------------|----------------------|-----------------|-----------|-----------------|------------------|
| △ | | | | APPROVED | CHECKED | MATERIAL 材料 | - | CHAMFER 一般面取 | - | QUANTITY 個数 | |
| △ | | | | T. A. | T. A. | TREATMENT 処理 | - | FINISHING 仕上 | - | - | |
| △ | | | | | | TREATMENT CONTACT 処理接点 | - | DECENTRATION 偏芯 | - | | |
| △ | | | | DESIGNED | DRAWN | OVER 250 UP TO 1000 | ±0.3 ±0.5 ±1.0 ±0.2 | ANGLE 角度 | METHOD 図法 | REMARK 適用 (機種名) | |
| △ | | | | T. A. | T. T. | OVER 63 UP TO 250 | ±0.2 ±0.3 ±0.6 ±0.15 | UNIT (mm) | - | SV-1614HF | |
| △ | | | | | | OVER 16 UP TO 63 | ±0.1 ±0.2 ±0.4 ±0.1 | | | | SCALE |
| △ | | | | | | OVER 0 UP TO 16 | ±0.05 ±0.1 ±0.2 ±0.1 | DATE | '13.03.15 | DRAW NO. | 01D SV 01 28 A 1 |
| | DATE | EXCH NO. | REVISION 変更記事 | | | TOLERANCES | A B C S | | | | |

Mega Pixel CCTV Lens

| | |
|---------------------------|----------------------------------|
| Model | SV-1614HF |
| Focal Length | 16 mm (16.32) |
| Maximum Aperture Ratio | 1:1.4 (1.44) |
| F.No | F1.4 ~ F16 |
| Angle of view (2/3") | 22.9° × 30.2° (Diagonal: 37.3°) |
| M.O.D | 100 mm |
| Flange back | 17.526 mm |
| Operation of Iris & Focus | Manual |
| Mount | C-mount |
| Filter Thread | M35.5mm P=0.5 |
| TV distortion (2/3") | -0.20 % |
| Sensor size (max.) | 2/3" |
| Weight (approx.) | 125 g |
| Dimension | ϕ 39.5 (MAX) × L= 53.5 mm |