



The performance features at a glance

- 5.6" portable colour monitor
- Stereo sound
- Battery and mains operation
- Including signal generator to test cable lines
- Rechargeable long life Li-Po battery
- Auto power save function
- Nylon carrier bag with shoulder straps



High versatility

The 5.6" ZM-L406P-II colour monitor combines up-to-date technology with proven components. Thus, the service monitor offers its users an ideal tool to install, maintain, and start up surveillance cameras. The cable-free operation with a modern Li-Po battery offers independence from power sources for up to 2.5 hours. The service monitor can optionally also be used with a DC 9 V mains connection or can be recharged via an adapter on the cigarette lighter in the car.

Outstanding advantages

Two BNC video inputs and one audio input provide the necessary connectivity. In each case, one BNC video- and one audio-output are available for output signals. The service monitor can also be used as a signal generator to check cable lines.

High-performance technology

The portable ZM-L406P-II LCD colour monitor offers a 640x480 resolution, differential contrast and excellent brightness values which make it possible to work even in unfavourable light conditions. Furthermore, the monitor is equipped with stereo loudspeakers for corresponding audio signals.

Other special features

The ergonomic and easy handling is supported by lateral operating keys on the front. At the same time, the connection of A/V sources is very easy to handle due to the laterally fitted in- and outputs.

Order data

Order number	Product description
ZM-L406P-II	LCD/TFT, 5.6" (14.2 cm), 640 x 480 pixel, 9VDC/14W, 2xBNC inputs, 1 x BNC output, 1 x audio input/output (3.5 mm jack plug), built-in test image generator, incl. mains adapter, battery case, protective bag with belt

LCD colour monitor ZM-L406P-II



Advantages for the installer

The easy handling, the low weight and the supply in the well-designed service bag make the TFT LCD colour monitor with 5.6" screen size the ideal test monitor. Thanks to the supplied service bag with a shoulder strap, a two-handed adjustment is equally ensured. This also applies, if the camera is located in places which are difficult to access.

Technical specifications	ZM-L406P-II
LCD Display	5,6" TFT LCD Panel, 16.7M colors
Screen size	113 x 85mm
Max Resolution	640 x 480 (4:3)
Lamp lifetime	20,000 hours
Contrast ratio	500:1
Brightness	150 cd/m2
Response time Tr / Tf	10 / 15ms
Viewing angle L/R	70 degrees
Front control	Power on/off. Power/recharge LED indicator, Source, Up, Down, Picture
Display mode	Video1, Video2, Test pattern
OSD menu	Language, Auto off, Contrast, Brightness, Colour, Tint, Sharpness, Recall
Input	2X BNC Video input 1X 3,5mm Stereo Audio
Output	1x BNC Video output 1X3,5mm Stereo Audio
Audio speaker	1 Watt (max)
Environmental	0 - + 40 degrees centigrade
Power consumption	14 Watt
Power input	AC input 100-240 Volt AC
Dimensions (W x H x D)	190 x 126 x 44mm
Rechargeable battery	7,4 volt 2600mAh Li-Po