

# 4K UHD LED

## PD282-4KLED

## 4K UHD LED Monitor

### PD282-4KLED

Panel Type	28" (16:9) 4K LED Backlit Monitor
Case Type	Plastic
Maximum Resolution	3840 x 2160 @ 60Hz
Active Display Area	648.9 (H) X 369.3 (V)
Pixel Pitch	0.16 (H) x 0.16 (V)
Bezel Thickness	L/R/U: 20mm, D:26mm
Contrast Ratio	1000 : 1
Brightness	300 cd / m <sup>2</sup>
Response Time	5m.sec (G to G)
Viewing Angle	170 / 160 °
Display Colours	1.073B
Display Mode	16 : 9 / 4 : 3
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	16 : 9
VGA Auto Frequency Correction	Yes
Speakers	3W x 2
Number of Speakers	2
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	Yes

### IN / OUT INTERFACE

Video Interface	2 x HDMI v2.0 input 2 x DP v 1.2 input
Audio	PC audio out
Power Interface	DC in
Termination	75 ohm
Certification	CE, FCC, ROHS
VESA	100 x 100
Stand Type	Desk
Colour	Black
Button Position	Bottom right
Packing Dimensions	600 x 445 x 96mm
Nett Weight	6.0 Kgs
Gross Weight	6.9 Kgs



### POWER

Power Supply	12 v DC 5A
Voltage	110 / 230 AC
Power Consumption	45 watt (typical)

### OSD CONTROLS

Brightness, Contrast, Eco, DCR, H.Position, V. Position, Clock, Phase, Aspect, Colour Temp, OSD setting, OSD language, OSD H. Pos, OSD V. Pos, OSD timer, OSD Transparency, Factory Reset, Singal Source, Volume

### OSD LANGUAGE

English, French, German, Chinese Italian, Spanish, Portuguese, Turkish, Polish and Dutch.

### ACCESSORIES

Power cable, power adaptor, HDMI cable, User's manual

