



USA MADE



-40° TO +75°



IEEE802.3at



FLEXIBILITY



PORT GUARDIAN



UPLINKS



2



8



3



The ComNet CNGE3FE8MS has three 100/1000Base-FX SFP* ports and eight 10/100Base-TX ports. Two of the SFP ports support 2.5 Gbps SFPs for high speed communication in bandwidth intensive applications. All SFP ports utilize ComNet SFP modules for fiber and connector type and distance. The ComNet exclusive Port Guardian feature provides additional cyber security protection by enabling physical port lockout in the event that an existing cable is disconnected and prevents a potential network incursion using common spoofing techniques. The intrusion event is reported back to the operator using SNMP. The series offers multiple Ethernet redundancy protocols which protect your applications from network interruptions or temporary malfunctions by redirecting transmission within the network. The switch provides advanced IP-based management that can limit the maximum bandwidth for each connected IP device, allowing the user to adjust usage. The CNGE3FE8MSPOE models provide eight electrical ports supporting up to thirty watts of power. On the CNGE3FE8MSPOEHO model, four of the eight PoE ports can support up to sixty watts of PoE power. All PoE ports are IEEE802.3at compliant.

FEATURES

- › 3 × 100/1000Base-FX SFP
8 × 10/100Base-TX RJ45
- › 2 × SFP ports support 2.5 Gbps SFP modules for high speed communication
- › CNGE3FE8MSPOE provides 8 × IEEE802.3at compliant 30 W PoE+ ports
- › CNGE3FE8MSPOEHO provides 4 × IEEE802.3at compliant 30 W PoE+ ports and 4 × IEEE802.3at compliant 60 W PoE++ ports
- › CNGE3FE8MSPOE/24 provides low voltage 12-24VDC PoE booster function
- › Fast Redundancy/Recovery - MSTP/RSTP/STP (IEEE802.1s/w/D) and ERPS G.8032
- › Layer 3 static routing
- › Supports IPV6 new internet protocol version
- › Provided HTTPS/SSH protocol enhances network security
- › Supports Device Binding security function
- › Supports SNMP v1/v2c/v3 & RMON & 802.1Q VLAN Network Management
- › Supports ACL, 802.1x User Authentication for security
- › Supports 9.6K Bytes Jumbo Frame
- › Web-based, Telnet and Console (CLI) configuration, and Windows-based (eVision) monitoring
- › Designed for wall or DIN rail mount installations

SOFTWARE FEATURES

- › Port Guardian prevents network intrusion through intelligent physical port lockout
- › STP/RSTP/MSTP (IEEE 802.1D/w/s)
- › Ethernet Ring Protection Switching (ERPS) (G.8032)
- › Quality of Service (802.1p) for real-time traffic
- › VLAN (802.1Q) with VLAN tagging and GVRP supported
- › IGMP v2/v3 (IGMP snooping support) and MLD v1/v2 for filtering multicast traffic
- › Supports IP-based bandwidth management
- › Supports application-based QoS management
- › Port configuration, status, statistics, monitoring, security
- › DHCP Client/Server, DHCP Snooping, DHCP Relay
- › Custom User Access Rights (15 Levels)
- › Static and LACP Link Aggregation
- › Supports Loop Protection function
- › Multicast VLAN Registration (MVR)
- › Supports IP Multicast Profile (IPMC)
- › Link Layer Discovery Protocol (LLDP)
- › Voice VLAN support
- › UPNP (universal plug and play)

* Small Form-Factor Pluggable Module. Sold separately.

SPECIFICATIONS

AGENCY COMPLIANCE



Connectors

10/100Base-TX Ports	8 × RJ-45
100/1000Base-X Port	3 × SFP ¹
Serial Console Port	USB Type B Connector (115200bps, 8, N, 1)
Power	2 × 2-Pin Terminal Block
Fault Relay	3-Pin Terminal Block

Switch Properties

Switching latency	7 μs
Switching bandwidth	13.6 Gbps
DRAM	1GB
Flash	128Mb
VLANs	Voice, Private, Multicast
Max. Available VLANs	256
IGMP multicast groups	128 for each VLAN
Port rate limiting	User Defined
Processing	Store-and-Forward
Priority Queues	8
Network Redundancy	STP RSTP MSTP ERPS
MAC Table	8K MAC Addresses
Jumbo Frame	Up to 9.6K Bytes
Static Routing	32 Routes

Security Features

Device Binding security feature	SNMPv3 encrypted authentication and access security
Enable/disable ports, MAC based port security	https / SSH enhance network security
Port based network access control (802.1x)	Switch/port based, NAS, ACL, ARP inspection and IP sourceguard
VLAN (802.1Q) to segregate and secure network traffic	AAA radius server authentication
Radius centralized password management	TACACS+ SNTP

Power

Input Power	Redundant 12 to 57 VDC (non-PoE model) Redundant 12 to 24 VDC (POE/24 model) Redundant 48 to 57 VDC (POE & POEHO models)
Power Consumption	10 W Max, non-PoE 250 W Max w/ PoE+ (POE model) 150 W Max w/PoE+ @ 24 VDC (POE/24 model) 120 W Max w/PoE+ @ 12 VDC (POE/24 model) 370 W Max w/ PoE++ (POEHO model)
Overload Current Protection	Present
Reverse Polarity Protection	Present

Mechanical

Indicating LEDs	Power/Fault Indicators Alarm Indicator RJ45 Port Indicator SFP Port Indicator PoE Indicators
Size (H × W × D)	6.0 × 3.5 × 4.5 in (15.24 × 8.89 × 11.43 cm)
Installation	DIN-Rail or Wall Mount
Weight	2.6 lb / 1.2 kg

Environmental

Storage Temperature	-40 to +85° C
Operating Temperature	-40 to +75° C
Operating Humidity	5% to 95% Non-condensing
MTBF	>100,000 hours

Ethernet Standards

- IEEE 802.3 for 10Base-T
- IEEE 802.3u for 100Base-TX and 100Base-FX
- IEEE 802.3ab for 1000Base-T
- IEEE 802.z for 1000Base-X
- IEEE 802.3x for Flow control
- IEEE 802.3ad for LACP (Link Aggregation Control Protocol)
- IEEE 802.3at for Power Sourcing Equipment (PSE) and PoE up to 30 watts per port (CNGE3FE8MSPOE and CNGE3FE8MSPOEHO Only)
- IEEE 802.1p for COS (Class of Service)
- IEEE 802.1Q for VLAN Tagging
- IEEE 802.1D for STP (Spanning Tree Protocol)
- IEEE 802.1w for RSTP (Rapid Spanning Tree Protocol)
- IEEE 802.1s for MSTP (Multiple Spanning Tree Protocol)
- IEEE 802.1x for Authentication
- IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)
- IEEE 802.3az Energy Efficient Ethernet
- ITU-T G.8032v1/v2 Ethernet Ring Protection Switching (ERPS)

Regulatory Compliance

EMI	FCC Part 15, CISPR (EN55022) class A
EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
Shock	IEC60068-2-27
Free Fall	IEC60068-2-32
Vibration	IEC60068-2-6
Safety	EN60950-1
Rail	EN50121-4

ORDERING INFORMATION

Part Number	Description	100/1000 SFP Ports ¹	10/100 RJ45 Ports	30W PoE+ Ports	60W PoE++ Ports
CNGE3FE8MS	Industrially Hardened 11 Port Managed Ethernet Switch	3	8	0	0
CNGE3FE8MSPOE	Industrially Hardened 11 Port Managed Ethernet Switch, 48 VDC Input	3	8	8	0
CNGE3FE8MSPOE/24	Industrially Hardened 11 Port Managed Ethernet Switch, 12-24 VDC Input	3	8	8	0
CNGE3FE8MSPOEHO	Industrially Hardened 11 Port Managed Ethernet Switch	3	8	4	4
Included Accessories (North America Only)	DC Plug-in Power Supply, 90-264 VAC, 50/60 Hz (Included with CNGE3FE8MS only, for benign 0 to 50°C applications. Hardened power supply available, consult factory)				
Options	ComNet Recommended Power Supply for PoE Units (Not Included, consult factory) User selection of ComNet SFP (see SFP Modules data sheet for product numbers and compatibility before ordering)				

[1] Multimode fiber needs to meet or exceed fiber standard ITU-T G.651. Single mode fiber needs to meet or exceed fiber standard ITU-T G.652
Complies with FDA Performance Standard for Laser Products, Title 21, Code of Federal Regulations, Subchapter J. In a continuing effort to improve and advance technology, product specifications are subject to change without notice.