



| | | | | | | | | | | | |
|--------|---------------------------|----------|-------|----------|---------|------------------------|----------------------|-----------------|-----------|-------------------------------|----------|
| △× | | | | APPROVED | CHECKED | MATERIAL 材料 | - | CHAMFER 一般面取 | - | QUANTITY 個数 | |
| △× | | | | T. A. | T. A. | TREATMENT 処理 | - | FINISHING 仕上 | - | - | |
| △× | | | | | | TREATMENT CONTACT 処理接点 | - | DECENTRATION 偏芯 | - | | |
| △× | | | | DESIGNED | DRAWN | OVER 250 UP TO 1000 | ±0.3 ±0.5 ±1.0 ±0.2 | ANGLE 角度 | METHOD 図法 | REMARK 適用 (機種名) | |
| △× 1 | rotation 表記追加 | 19.03.03 | T. F. | T. T. | S. K. | OVER 63 UP TO 250 | ±0.2 ±0.3 ±0.6 ±0.15 | UNIT (mm) | - | VS-TCM5-50C0 DRAWING / 外觀図 | |
| △× 1 | φ8(+0.02/0) → φ8.1(±0.05) | 18.08.29 | S. U. | | | OVER 16 UP TO 63 | ±0.1 ±0.2 ±0.4 ±0.1 | SCALE | 1 / 1 | | NAME |
| NO.×箇所 | REVISION 訂正事項 | DATE | NAME | | | OVER 0 UP TO 16 | ±0.05 ±0.1 ±0.2 ±0.1 | DATE | 11.05.13 | | DRAW NO. |
| | | | | | | TOLERANCES | A B C S | | | | |