

# WAT-3500

1/2.8" Multi-function Compact High Sensitivity Analog B&W Camera

Typical design model with multi-functions in a small body


**NEW**



## Key features

- 1/2.8-inch BSI CMOS image sensor with high sensitivity
- Advanced setting available by OSD (On Screen Display) through an optional remote controller
- Min. illumination 0.0001 lx F1.4 (AGC HIGH=72dB, Shutter=OFF)  
0.000007 lx F1.4 (AGC HIGH=72dB, Shutter=x15)

## Dimensions



## Specifications

Video standard		EIA	CCIR
Pick-up element		1/2.8 inch BSI CMOS image sensor	
Number of effective pixels		1945(H) × 1097(V) *1	
Unit cell size		2.9µm(H) × 2.9µm(V)	
Imaging system		-	
Synchronizing system		Internal	
Scanning system		Progressive	
Video output		Composite: 1.0 V(p-p) 75Ω (Unbalanced)	
Setup level		7.5IRE	0IRE
Resolution (H)		More than 570TVL (Center)	
Minimum illumination		0.0001 lx F1.4 (AGC HIGH=72dB, Shutter=OFF)	
		0.000007 lx F1.4 (AGC HIGH=72dB, Shutter=x15)	
S/N		More than 45dB (AGC OFF=0dB, γ=1.0)	
Function settings		OSD : Remote controller	
AE mode	Fixed	x2, x3, x4, x5, x6, x7, x8, x9, x10, x12, x15 (frame)	
		1/30, 1/60, 1/120, 1/180, 1/240, 1/300 sec.	1/25, 1/50, 1/100, 1/150, 1/200, 1/250 sec.
	EI	1/500, 1/1000, 1/2000, 1/5000, 1/10000 sec.	1/25 - 1/10000 sec.
White balance		x15 - 1/10000 sec.	
AGC	ON	0 - 36dB (LOW), 0 - 50dB (MID), 0 - 72dB (HIGH)	
	OFF	0dB	
MGC		0 - 72dB (5dB step)	
Day/Night		-	
Gamma characteristics		γ≠USER (Level adjustable)	
Video level		-	
Noise reduction		3DNR OFF/ON Level adjustable, 2DNR OFF/ON Level adjustable, 3D+2DNR ON Level adjustable	
Wide dynamic range		WDR OFF/ON Level adjustable, D-WDR OFF/ON Level adjustable	
Lens iris		DC	
Back light compensation		BLC, HSBLC	
White blemish correction		Up to 2046 pixels	
Sharpness		OFF/ON Level adjustable	
Defog		OFF/ON Level adjustable	
Digital zoom		ZOOM (x1.01 - x6.00), PAN/TILT	
Privacy mask		8 masks	
Mirror image		OFF, V-FLIP, H-FLIP, HV-FLIP	
Freeze		OFF/ON	
Motion detection		-	
Neg.image		OFF/ON	
Interface		BNC (Composite video), Power in, Remote controller (RC-01), Auto iris	
Power supply		DC+12V±10%	
Power consumption		2.52W (210mA)	
Operating / Storage temperature		-10 - +50°C / -30 - +70°C	
Operating / Storage humidity		95%RH or less (Without condensation)	
Lens mount		CS mount (Back focus adjustable)	
Weight		Approx. 78g	
Accessories		WPDC12 (DC plug), Hex. wrench	
Acquired Standards		FCC *2	

\*1: The output is cut out according to the video standard. \*2: CE standard is not acquired.

Accessories Options

**CS-mount lenses**

M13VG288IR M13VG850IR  
AG3Z2812FCS-MPWIR AG4Z1214FCS-MPIR


**Miniature lenses / Mount adaptors**

M2520BC-12 M2920BC-12  
M3620BC-12 M0620BC-12 28MMA-M12-155  
M1625BC-12


**C-mount lenses**

\*Not in our lineup  
C-mount adaptor  
30CMA-R

**WAT-3500**



VIDEO OUT (BNC)



OSD

**Cable**

3C2V (BNC/BNC)  
3C2V (BNC/RCA)

BNC  
RCA

Monitor  
\*Not in our lineup

POWER IN (DC+12V)

**Power supply adaptors**

SWI12-12-N-P5  
SWI12-12-E-P5

**Remote controller**

RC-01

**Stands**

MS50 WH-31 WH-11 WH-21

**Water resistant camera housing / Mounting brackets**

VCHO-15S WH-6N PTP-300